#201LS Bulldog Low Solids Silicone







1. PRODUCT AND COMPANY IDENTIFICATION

1.1. Product identifier

Product Identity

Alternate Names

Bulldog Silicone Coating #201LS

Bulldog Silicone Coating #201LS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use See Technical Data Sheet
Application Method See Technical Data Sheet

1.3. Details of the supplier of the safety data sheet

Company Name Palmer Asphalt Company

196 West 5th St., P.O. Box 58

Bayonne, NJ 07002

Emergency Telephone No. (201) 339-0855

8:00a.m. - 5:00p.m. EST

After Hours CHEMTREC:

(800) - 424-9300 (Domestic - No. America)

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Product Description: This product is a viscous liquid in various colors including white, tan, light gray and dark gray with a slight odor. **Health Hazards:** Exposure to the product may cause skin and eye irritation. Prolonged exposure may cause skin sensitization. Ingestion is not a normal route of exposure under normal product use. If swallowed, product may cause gastrointestinal irritation. This product contains an ingredient that is suspected of causing cancer. **Flammability Hazards:** This product has a flash point of >95°F and does not sustain combustion. **Reactivity Hazards:** None known. **Environmental Hazards:** The environmental effects of this product have not been investigated; however it is not expected to cause adverse effects in the environment. **Emergency Considerations:** Emergency responders must wear the proper personal protective equipment (and haveappropriate fire-suppression equipment) suitable for the situation to which they are responding. **PICTOGRAMS**



SIGNAL WORD: Danger

GHS CLASSIFICATION OF SUBSTANCE OR MIXTURE IN ACCORDANCE WITH 29 CFR 1200 (OSHA HCS) AND THE EUROPEAN UNION DIRECTIVES: This product does meet the definition of a hazardous substance or preparation as defined by 29 CFR 1910. 1200 AND the European Union Council Directives 67/548/EEC, 1999/45/EC, 1272/2008/EC and subsequent Directives. EU HAZARD CLASSIFICATION OF INGREDIENTS:

EC# 265-149-8 Annex VI Index# 649-422-00-2

EC# 236-675-5 This substance is not classified in the Annex VI EC# 245-366-4 This substance is not classified in the Annex VI EC# 601-216-3 This substance is not classified in the Annex VI EC# 217-164-6 This substance is not classified in the Annex VI Component(s) Contributing to Classification(s) Nepheline Syenite, Distillates (petroleum), hydrotreated light, Titanium Dioxide, 2-Butanone,O,O', O"- (Methylsilylidyne)Trioxime, Silica, Amorphous, fumed, crystal-free, N-(3-(Trimethoxysilyl)-1,2-ethanediamine

GHS Hazard Classification(s):

Skin Irritation Category 2 Eye Irritation Category 2A
Skin Sensitization Category 1 Carcinogenicity Category 2
Specific Target Organ Toxicity Category 3 (Respiratory Irritation) Aspiration Hazard Category 1

#201LS Bulldog Low Solids Silicone

SDS Revision Date: 4/12/2021





Hazard Statement(s):

H315: Causes skin irritation

H319: Causes serious eye irritation

H317: May cause and allergic skin reaction H351: Suspected of causing cancer

H335: May cause respiratory irritation.

H304: May be fatal if swallowed and enters airways

Prevention Statement(s):

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood. P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product. P271: Use only outdoors or in a well-ventilated area.

P272: Contaminated work clothing should not be allowed out of the workplace. P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response Statement(s):

P308+P313: IF exposed or concerned: Get medical advice/attention. P302+P352: IF ON SKIN: Wash with plenty of water. P321: Specific treatment (See Section 4 of this SDS).

P333+P313: If skin irritation or rash occurs: Get medical advice/attention. P362+P364: Take off contaminated clothing and wash it before reuse.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312: Call a POISON

CENTER/doctor if you feel unwell.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331: Do NOT induce vomiting.

Storage Statement(s):

P403+P233: Store in a well-ventilated place. Keep container tightly closed. P405: Store locked up.

Disposal Statement(s):

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

HEALTH HAZARDS OR RISKS FROM EXPOSURE:

This product does not meet the criteria for PBT or vPvB in accordance with Annex XIII

ACUTE: This material may cause irritation to skin, eye, and respiratory system. May cause skin sensitization. Ingestion of this product may cause gastrointestinal irritation. This product contains an ingredient(s) that are suspected of causing reproductive harm.

CHRONIC: Prolonged or repeated skin contact may cause skin reactions.

TARGET ORGANS: ACUTE: Eye, Skin, Respiratory System CHRONIC: Respiratory System

#201LS Bulldog Low Solids Silicone





3. COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS:	CAS#	EINECS#	ICSC#	WT %	HAZARD CLASSIFICATION
Distillates (petroleum), hydrotreated light	64742-47-8	265-149-8	1379	10-20%	FLAM LIQ CAT 3, SKIN IRRIT CAT 2, EYE IRRIT CAT 2A, STOT SE CAT 3, ASP HAZ CAT 1
Titanium Dioxide	13463-67-7	236-675-5	0338	5 – 15%	CARC. CAT 2
2-Butanone,O,O', O"- (Methylsilylidyne)Trioxime	22984-54-9	245-366-4	Not Listed	2 – 7%	SKIN IRRIT CAT 2, EYE IRRIT. CAT 2A, SKIN SENS CAT 1
Silica, Amorphous, fumed, crystal-free	112945-52-5	601-216-3	Not Listed	1 – 3%	SKIN IRRIT CAT 2, EYE IRRIT. CAT 2A, STOT SE CAT 3 (RESP IRRIT)
N-(3-(Trimethoxysilyl)-1,2- ethanediamine	1760-24-3	217-164-6	Not Listed	0.1-1%	ACUTE TOX 4 (ORAL, INHAL) SKIN IRRITCAT 2, EYE IRRIT. CAT 2A, SKIN SENS CAT 1
Balance of other ingredients are non-hazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).					

^{*} Ingredients are Company Trade Secret - Business Confidential. Palmer Asphalt Company is withholding the specific chemical information under provision of the OSHA Hazard Communication Rule Trade Secrets (1910.1200(i)(1)). The specific chemical information will be made available to health professionals in accordance with 29 CFR 1910.1200 (i)(1) (2) (3) (4)..

SECTION 4 - FIRST-AID MEASURES

4. FIRST AID MEASURES

EYE CONTACT: If product enters the eyes, open eyes while under gentle running water for at least 15 minutes. Seek medical attention if irritation develops.

SKIN CONTACT: Wash skin thoroughly after handling. Seek medical attention if irritation develops and persists. Remove contaminated clothing. Launder contaminated clothing before re-use.

INHALATION: If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention if breathing dificulty continues.

INGESTION: If product is swallowed, call physician or poison control center for most current information. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. Seek medical advice. Take a copy of the label and/or MSDS with the victim to the health professional.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing skin, or eye problems may be aggravated by exposure to this product.

RECOMMENDATIONS TO PHYSICIANS: Treat symptoms and reduce over-exposure.

#201LS Bulldog Low Solids Silicone

SDS Revision Date: 4/12/2021





5. FIRE FIGHTING MEASURES

FLAMMABLE LIMITS (in air by volume, %):

Lower (LEL):

Not Established

Upper Not Established

(UEL):

FIRE EXTINGUISHING MATERIALS:

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Explosion Sensitivity to Mechanical Impact: Explosion Sensitivity to Static Discharge: SPECIAL FIRE-FIGHTING PROCEDURES:

Carbon dioxide, foam, dry chemical, halon, water spray, sand, limestone powder.

This material has been tested to ASTM D-4206 Standard and found not to sustain combustion


Not Sensitive. Not Sensitive

Incipient fire responders should wear eye protection. firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done

without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of

water, or other environmentally sensitive areas.

NFPA RATING SYSTEM



HMIS RATING SYSTEM

	TIMIO NATINO OTOTEM					
H/	HAZARDOUS MATERIAL IDENTIFICATION SYSTEM					M
	HEALTH HAZARD (BLUE)					
	FLAMMABILITY HAZARD (RED) 2					
	PHYSICAL HAZARD (YELLOW)					
	PROTECTIVE EQUIPMENT					
	EYES RESPIRATORY HANDS BODY				DY	
	F)	See Sect 8		See Sect 8		
	For Routine Industrial Use and Handling Applications					•

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

6. ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK RESPONSE: Personnel should be trained for spill response operations SPILLS: Contain spill if safe to do so. Prevent entry into drains, sewers, and other waterways. Soak up with a noncombustible absorbent material and place in an appropriate container for disposal. Dispose of in accordance with applicable Federal, State, and local procedures (see Section 13, Disposal Considerations)

#201LS Bulldog Low Solids Silicone







7. HANDLING AND STORAGE

WORK PRACTICES AND HYGIENE PRACTICES: As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash thoroughly after handling this product. Do not eat, drink, smoke, or apply cosmetics while handling this product. Avoid breathing vapors/mists generated by this product. Use in a well-ventilated location. Remove contaminated clothing immediately.

STORAGE AND HANDLING PRACTICES: Keep container tightly closed and in a dry and cool place.

8. EXPOSURE CONTROLS\PERSONAL PROTECTION

EXPOSURE LIMITS/GUIDELINES:

Chemical Name	CAS#	ACGIH TWA	OSHA TWA	WEEL
Distillates (petroleum), hydrotreated light	64742-47-8	10 mg/m³	10 mg/m³	10 mg/m³
Titanium Dioxide	13463-67-7	10 mg/m³	10 mg/m³	10 mg/m³
2-Butanone,O,O', O"- (Methylsilylidyne)Trioxime	22984-54-9	Not Listed	Not Listed	Not Listed
Silica, Amorphous, fumed, crystal- free	112945-52-5	Not Listed	Not Listed	Not Listed
N-(3-(Trimethoxysilyl)-1,2- ethanediamine	1760-24-3	Not Listed	Not Listed	Not Listed

Currently, International exposure limits are not established for the components of this product. Please check with competent authority in each country for the most recent limits in place.

VENTILATION AND ENGINEERING CONTROLS: Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above. Use local exhaust ventilation to control airborne vapor. Ensure eyewash/safety shower stations are available near areas where this product is used.

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standard of Canada, or standards of EU member states(including EN 149 for respiratory PPE, and EN 166 for face/eye protection), and those of Japan. Please reference applicable regulations and standards for relevant details.

RESPIRATORY PROTECTION: Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states.

EYE PROTECTION: Safety glasses or chemical goggles as appropriate to prevent eye contact. If necessary, refer to U.S. OSHA 29 CFR 1910.133 or appropriate Canadian Standards.

HAND PROTECTION: Use chemical resistant gloves to prevent skin contact. If necessary, refer to U.S. OSHA 29 CFR 1910.138 or appropriate Standards of Canada.

BODY PROTECTION: Use body protection appropriate to prevent contact (e.g. lab coat, overalls). If necessary, refer to appropriate Standards of Canada, or appropriate Standards of the EU, Australian Standards, or relevant Japanese Standards.

#201LS Bulldog Low Solids Silicone





9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

APPEARANCE & ODOR: Viscous liquid in various colors including white, tan, light gray and dark gray with a

slight odor.

ODOR THRESHOLD (PPM): Not Available

>95°F (This product has been tested to the ASTM D-4206

FLASH POINT: Standard and determined that it does not sustain combustion)

AUTOIGNITION TEMPERATURE: Not Established VAPOR PRESSURE (mmHg): Not Available VAPOR DENSITY: Not Available EVAPORATION RATE (nBuAc = 1): Not Available BOILING POINT (C°): Not Available FREEZING POINT (C°): Not Available Not Available SPECIFIC GRAVITY 20°C: (WATER =1) Not Available SOLUBILITY IN WATER (%) Not Available **EXPLOSIVE PROPERTIES:** Not Available OXIDISING PROPERTIES: Not Available

10. STABILITY AND REACTIVITY

STABILITY: Product is stable

DECOMPOSITION PRODUCTS: When heated to decomposition this product produces noxious gases such as CO,

CO₂, and others.

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: None known

HAZARDOUS POLYMERIZATION: Will not occur.
CONDITIONS TO AVOID: Heat and sources of ignition.

11. TOXICOLOGICAL INFORMATION

TOXICITY DATA: Toxicity data is available for this product:

CAS# 13463-67-7 LD50 Acute Oral >10000 mg/kg Rat
CAS# 112945-52-5 LD50 Acute Oral 3160 mg/kg Rat
CAS# 64742-47-8 LD50 Acute Oral >5000 mg/kg Rat
CAS# 64742-47-8 LD50 Acute Dermal >2000 mg/kg Rabbit

Acute toxicity	Based on available data, the classification criteria are not met
Skin corrosion / irritation	Skin Irritation Category 2
Serious eye damage / irritation	Eye Irritation Category 2A
Respiratory or skin sensitization	Skin Sensitization Category 1
Germ cell mutagenicity	Based on available data, the classification criteria are not met
Carcinogenicity	Carcinogenicity Category 2
Reproductive toxicity	Based on available data, the classification criteria are not met
STOT-single exposure	Specific Target Organ Toxicity – Single Exposure (Respiratory Irritation)
STOT-repeated exposure	Based on available data, the classification criteria are not met
Aspiration hazard	Aspiration Hazard Category 1

#201LS Bulldog Low Solids Silicone

SDS Revision Date: 4/12/2021





SUSPECTED CANCER AGENT: One or more of the ingredients are found on the following lists: FEDERAL OSHA Z LIST,

NTP, CAL/OSHA, IARC and therefore are considered to be, or suspected to be a cancer-causing agent by these agencies.

Titanium dioxide (13463-67-7)

ACGIH: A4 – Not classifiable as a Human Carcinogen

NIOSH: Potential occupational carcinogen

IARC: Monograph 93 posted, Monograph 47 [1989] (Group 2B (possibly carcinogenic to humans))

IRRITANCY OF PRODUCT: Contact with this product can be irritating to exposed skin, eyes, and respiratory system.

SENSITIZATION OF PRODUCT: This product is considered a skin sensitizer.

REPRODUCTIVE TOXICITY INFORMATION: No reported information concerning the effects of this product and its

components on the human reproductive system.

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE: Causes respiratory irritation.

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE: None known

ASPIRATION HAZARD: None

12. ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

TOXICITY: No specific data is currently available on this product's effects on aquatic life.

PERSISTENCE AND DEGRADABILITY: No specific data available on this product.

BIOACCUMULATIVE POTENTIAL: No specific data available on this product.

MOBILITY IN SOIL: No specific data available on this product.

RESULTS OF PBT AND vPvB ASSESMENT: No specific data available on this product.

OTHER ADVERSE EFFECTS: No specific data available on this product.

WATER ENDANGERMENT CLASS: Not believed to be water endangering in accordance with EU Guideline 91/155-EWG.

At present there are no ecotoxicological assessments for this product.

13. DISPOSAL CONSIDERATIONS

PREPARING WASTES FOR DISPOSAL: Waste disposal must be in accordance with appropriate Federal, State, and local regulations, those of Canada, Australia, EU Member States and Japan.

RCRA WASTE CODE: None listed EU WASTE CODE: Not Listed

14. TRANSPORT INFORMATION

US DOT; IATA; IMO; ADR:

THIS PRODUCT IS CLASSIFIED AS DANGEROUS GOODS AS DEFINED BY 49 CFR 172.101 BY THE U.S.DEPARTMENT OF TRANSPORTATION.

This product has been tested to the ASTM D-4206 Standard and determined that it does not sustain combustion. As resultit is exempt from regulations when shipped ground or rail within the U.S.A.

PROPER SHIPPING NAME: Non-Regulated when shipped ground or rail with U.S.A.

HAZARD CLASS NUMBER and DESCRIPTION: None

UN IDENTIFICATION NUMBER: None

PACKING GROUP: None

DOT LABEL(S) REQUIRED: None

NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER (2016): None

MARINE POLLUTANT: This product's ingredients that are not classified by the DOT as a Marine Pollutant (as defined by 49 CFR 172.101, Appendix B)

TRANSPORT CANADA, TRANSPORTATION OF DANGEROUS GOODS REGULATIONS:

#201LS Bulldog Low Solids Silicone



SDS Revision Date: 4/12/2021



This product is not classified as Dangerous Goods, per regulations of Transport Canada. INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA):

This product is not classified as Dangerous Good by International Air Transport.

INTERNATIONAL MARITIME ORGANIZATION (IMO) DESIGNATION:

This product is not classified as Dangerous Goods by the International Maritime Organization.

EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY ROAD (ADR):

This product is not classified by the United Nations Economic Commission for Europe to be dangerous goods. Harmonized Tariff Code Not Listed

15. REGULATORY INFORMATION

UNITED STATES REGULATIONS

SARA REPORTING REQUIREMENTS: This product is not subject to the reporting requirements of Sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act., as follows: None

TSCA: All components in this product are listed on the US Toxic Substances Control Act (TSCA) inventory of chemicals.

SARA 311/312:

Acute Health: Yes Chronic Health: Yes Fire: No Reactivity: No

U.S. SARA THRESHOLD PLANNING QUANTITY: There are no specific Threshold Planning Quantities for this product. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) may apply, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITY (RQ): None

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65):

WARNING This product contains Titanium Dioxide which is known to the State of California as a cancer hazard if in respirable form.

CANADIAN REGULATIONS:

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS: No

component of this

product is on the CEPA First Priorities Substance Lists.

CANADIAN WHMIS CLASSIFICATION and SYMBOLS: Classified per WHMIS 2015

EUROPEAN ECONOMIC COMMUNITY INFORMATION:

EU LABELING AND CLASSIFICATION:

Classification of the mixture according to Regulation (EC) No1272/2008. See section 2 for details.

AUSTRALIAN INFORMATION FOR PRODUCT:

AUSTRALIAN INVENTORY OF CHEMICAL SUBSTANCES (AICS) STATUS: All components of this product are listed or exempt from listing on the AICS.

STANDARD FOR THE UNIFORM SCHEDULING OF DRUGS AND POISONS: Not applicable.

JAPANESE INFORMATION FOR PRODUCT:

JAPANESE MINISTER OF INTERNATIONAL TRADE AND INDUSTRY (MITI) STATUS: The components of this product

are not listed as Class I Specified Chemical Substances, Class II Specified Chemical Substances, or Designated Chemical Substances by the Japanese MITI.

Bulldog Silicone Coating #201LS

SDS Revision Date: 4/14/2021





INTERNATIONAL CHEMICAL INVENTORIES:

Listing of the components on individual country Chemical Inventories is as follows:

Asia-Pac:

Australian Inventory of Chemical Substances (AICS):

Korean Existing Chemicals List (ECL):

Japanese Existing National Inventory of Chemical Substances (ENCS):

Philippines Inventory if Chemicals and Chemical Substances (PICCS):

Swiss Giftliste List of Toxic Substances:

U.S. TSCA:

Listed or exempt from listing

16. OTHER INFORMATION

MANUFACTURER DISCLAIMER: Palmer Asphalt Company warrants only that its products meet the specifications stated in the sales contract. Typical properties, where stated, are to be considered as representative of current production and should not be treated as specifications. While all the information presented in this document is believed to be reliable and to represent the best available data on these products, NO GUARANTY, WARRANTY, OR REPRESENTATION IS MADE, INTENDED, OR IMPLIED AS TO THE CORRECTNESS OR SUFFICENCY OF ANY INFORMATION, OR AS TO THE MERCHANTABILITY OR SUITABILITY OR FITNESS OF ANY CHEMICAL COMPOUNDS OR OTHER PRODUCTS OR THE USE THEREOF ARE NOT SUBJECT TO A CLAIM BY A THIRD PARTY FOR INFRINGMENT OF ANY PATENT OR OTHER INTELLECTUAL PROPERTY RIGHT. THE USER SHOULD CONDUCT SUFFICIENT INVESTIGATION TO ESTABLISH THE SUITABILITY OF ANY PRODUCT FOR ITS INTENDED USE - Liability of Palmer Asphalt Company for all claims, whether arising out of breach of warranty, negligence, strict liability, or otherwise, is limited to the purchase price of the material. Products may be toxic and require special precautions in handling. For all products listed, the user should obtain detailed information on toxicity, together with proper shipping, handling, and storage procedures, and comply with all applicable safety and environmental standards. Toxicity and risk characteristics of chemical compounds and other products may differ when used with other materials or in a manufacturing or other process. Those risk characteristics should be determined by the user and made known to handlers, processors, and end users. End of SDS