

#110 BULLDOG® NON-FIBERED ROOF COATING (ROOF PAINT)



DESCRIPTION

A high quality, ductile non-fibered black asphalt that is furnished ready to use. It provides a tough waterproof film and may be used in many disparate applications.

USES

A very good protective paint for metal decks or roofs. Can be used to dampproof masonry surfaces and to protect metal and wood gutters. Use as saturant on dry asphalt composition roofs.

METHODS AND RATE OF APPLICATION

Apply with brush, roller or spray to dry, sound, dirt and grease free surfaces in uniform moderate coat. Use one gallon per 100 square feet (.4 liters per M²) on asphalt composition or masonry surfaces and 2/3 gallon per 100 square feet (.26 liter per M²) on metal. DO NOT THIN. COVER AIR INTAKES BEFORE APPLYING AND WHILE CURING.

CONTAINER SIZE	APPROXIMATE SHIPPING WEIGHTS
55 Gallon Drum	475 POUNDS
5 Gallon Pail	42 POUNDS

TYPICAL PHYSICAL CHARACTERISTICS

Nonvolatile Matter, % Solids by Weight	72.0
Volatile Solvent, % by Weight	28.0
Asphalt Solids, % by Volume	72.0
Water Content, % by Volume	0.5
Net Weight Per Gallon, Pounds	7.8
Dry Film Thickness Without Absorption Applied at Rate of 100 Square Feet Per Gallon9 MILS
Dry Time @ Recommended Rate of Application	2 Days
Service Temperature	-30°F to +140°F
Flash Point, in Degrees F., C.C., ASTM D 93	104
Condition in Container	Homogeneous
Clean Up of Tools	Use Mineral Spirits or #99 BULLDOG Asphalt Remover

COPYRIGHT © PALMER ASPHALT COMPANY 4-08

The typical characteristics shown for this product are based upon the average of test results conducted on the finished product and on the raw material components used. They are subject to production variations and may be changed without notice. All other information contained on this sheet is to be used as a guide. For proper use and application please observe instructions and cautions on container.

DISCLAIMER OF WARRANTIES . The application procedures and other information contained herein or on any other literature or on the labels of any of our products is intended to provide a guide for the general use, handling, and storage of products produced by Palmer Asphalt Company and is based upon ideas that are well tested and believed to be reliable. Palmer Asphalt Company hereby disclaims all warranties, either expressed or implied, since it cannot control workmanship, weather, quality of other materials used, and other variables that might affect the results. Liability under this warranty is limited to the replacement of our material or refund of its cost at our option. This Company does not authorize any agent or any representative to make any warranty.

PALMER ASPHALT COMPANY
 196 WEST 5TH ST
 P.O. BOX 58
 BAYONNE, NJ 07002
 PHONE (201) 339-0855
 FAX (201) 339-8320
www.palmerasphalt.com