

#92AF BULLDOG® COAL TAR ROOF CEMENT



DESCRIPTION

A heavy trowel consistency roofing mastic blended from select coal tar and mineral fillers. Material remains pliable and is self-heating.
 SPECIFICATIONS: ASTM D 5643

USES

Useful as all purpose roof cement for repairs of cracks, splits, blisters in coal tar built up flat roofs. Do not use on steep surfaces. **This material has a strong odor.**

For exterior use only.

Do not use on asphalt surfaces.

METHODS AND RATE OF APPLICATION

Use a trowel to apply to clean dry surface. Apply approximately 1/8 inch (3.2mm) thickness. One gallon will cover 13 square feet (1.2 square Meters).
 COVER AIR INTAKES BEFORE APPLYING AND WHILE CURING.

CONTAINER SIZE	APPROXIMATE SHIPPING WEIGHTS
5 Gallon Pail	52 POUNDS

TYPICAL PHYSICAL CHARACTERISTICS

Mineral Filler and/or other Stabilizers, % by Weight.....	15
Solids, % by Weight.....	85
Dry Film Thickness Without Absorption Applied at Rate of 13 Square Feet Per Gallon	100 Mils
Net Weight Per Gallon.....	9.5 lbs
Flash Point, in Degrees F., C.C., ASTM D 93	105 Minimum
Condition in Container	Homogeneous
Clean-up of Skin	Waterless Hand Cleaner
Clean Up of Tools.....	Use Mineral Spirits or #99 BULLDOG Asphalt Remover

COPYRIGHT © PALMER ASPHALT COMPANY 4-08

The typical characteristics shown for this product are based upon the average of test results conducted on the finished product and on the raw material components used. They are subject to production variations and may be changed without notice. All other information contained on this sheet is to be used as a guide. For proper use and application please observe instructions and cautions on container.

DISCLAIMER OF WARRANTIES . The application procedures and other information contained herein or on any other literature or on the labels of any of our products is intended to provide a guide for the general use, handling, and storage of products produced by Palmer Asphalt Company and is based upon ideas that are well tested and believed to be reliable. Palmer Asphalt Company hereby disclaims all warranties, either expressed or implied, since it cannot control workmanship, weather, quality of other materials used, and other variables that might affect the results. Liability under this warranty is limited to the replacement of our material or refund of its cost at our option. This Company does not authorize any agent or any representative to make any warranty.

PALMER ASPHALT COMPANY
 196 WEST 5TH ST
 P.O. BOX 58
 BAYONNE, NJ 07002
 PHONE(201) 339-0855
 FAX (201) 339-8320
www.palmerasphalt.com