

#201 BULLDOG® ASPHALT SATURATED COTTON FABRIC



DESCRIPTION

A general purpose reinforcing membrane. Strong and flexible cotton fibers are saturated through with waterproofing asphalts to provide an open mesh fabric that is used in conjunction with asphalt coatings and cements in roofing, dampproofing and waterproofing work.

USES

Use for repairing cuts on roof when blisters are removed, for sealing cracks, laps and seams, for protecting flashings and parapets. Use for below grade waterproofing and dampproofing of foundations in new construction. May be used in many different patching and repair applications.

METHODS AND RATE OF APPLICATION

Simply tear or cut fabric in desired length and imbed in BULLDOG Heavy Duty Flashing Cement for patching or resealing seams, laps or flashing. Available in widths of 4, 6, 9, 12, 18 and 36 inches. All rolls are 150 feet long.

SIZE OF ROLL	ROLLS PER CARTON	SHIPPING WEIGHT
4"	12	27 POUNDS
6"	8	27 POUNDS
9"	4	19 POUNDS
12"	4	27 POUNDS
18"	2	19 POUNDS
36"	1	19 POUNDS

TYPICAL PHYSICAL CHARACTERISTICS

Saturating Material	Asphalt
Square Yard Saturated Weight, Ounces	5.7
Breaking Strength of Standard Fabric	
Warp	44.0
Fill	20.0
Thread Count	
Warp	28.0
Fill	14.0

COPYRIGHT © PALMER ASPHALT COMPANY 4-08

The typical characteristics shown for this product are based upon the average of test results conducted on the finished product and on the raw material components used. They are subject to production variations and may be changed without notice. All other information contained on this sheet is to be used as a guide. For proper use and application please observe instructions and cautions on container.

DISCLAIMER OF WARRANTIES . The application procedures and other information contained herein or on any other literature or on the labels of any of our products is intended to provide a guide for the general use, handling, and storage of products produced by Palmer Asphalt Company and is based upon ideas that are well tested and believed to be reliable. Palmer Asphalt Company hereby disclaims all warranties, either expressed or implied, since it cannot control workmanship, weather, quality of other materials used, and other variables that might affect the results. Liability under this warranty is limited to the replacement of our material or refund of its cost at our option. This Company does not authorize any agent or any representative to make any warranty.

PALMER ASPHALT COMPANY
 196 WEST 5TH ST
 P.O. BOX 58
 BAYONNE, NJ 07002
 PHONE(201) 339-0855
 FAX (201) 339-8320
www.palmerasphalt.com