

#112 BULLDOG®/DUREX STAIN BLOCK PRIMER



DESCRIPTION

A water based primer – sealer manufactured with acrylic resins.

- * meets all VOC regulations
- * low odor
- * easy clean up with soap and water

USES

#112 DUREX Stain Block Primer is used as a barrier to limit and prevent asphalt from staining and bleed through of white roof coatings. This product can also be used to seal transite panels. Seals chalky asphalt surfaces. Used when newly applied asphalt coatings or membranes require a white reflective roof coating.

METHOD AND RATE OF APPLICATION

All surfaces must be clean and free of dirt, dust, oil, and any contaminants that can interfere with adhesion. Power washing the roof is recommended. Do not power wash transite panels.

This material is ready to use and requires no agitation prior to use. Apply by roller or spray in a uniform manner.

Coverage: Apply at the rate of 1 gallon per 100 square feet. On porous substrates application rate may need to be increase. It is suggested that a minimum of 10% be added to area to be coated when calculating material requirements.

Drying Time: Depending upon temperature, direct sunlight, dew and relative humidity allow a minimum of 2- 4 hours dry time prior to application of DUREX Elastomeric Coatings.

Do not apply below 40°F or at relative humidity levels greater than 90%.

| CONTAINER SIZE | APPROXIMATE SHIPPING WEIGHTS |
|----------------|------------------------------|
| 5 Gallon Pail | 46 POUNDS |

Copyright © Palmer Asphalt Company 5-08

The typical characteristics shown for this product are based upon the average of test results conducted on the finished product and on the raw material components used. They are subject to production variations and may be changed without notice. All other information contained on this sheet is to be used as a guide. For proper use and application please observe instructions and cautions on container.

DISCLAIMER OF WARRANTIES . The application procedures and other information contained herein or on any other literature or on the labels of any of our products is intended to provide a guide for the general use, handling, and storage of products produced by Palmer Asphalt Company and is based upon ideas that are well tested and believed to be reliable. Palmer Asphalt Company hereby disclaims all warranties, either expressed or implied, since it cannot control workmanship, weather, quality of other materials used, and other variables that might affect the results. Liability under this warranty is limited to the replacement of our material or refund of its cost at our option. This Company does not authorize any agent or any representative to make any warranty.

PALMER ASPHALT COMPANY
196 WEST 5TH ST
P.O. BOX 58
BAYONNE, NJ 07002
PHONE(201) 339-0855
FAX (201) 339-8320
www.palmerasphalt.com