#205 Bulldog One Coat Silicone Coating for Residential Roofs

SDS Revision Date: 6/28/2022



SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

1.1. Product identifier

Product Identity #205 Bulldog One Coat Silicone Coating For Residential Roofs
Alternate Names #205 Bulldog One Coat Silicone Coating For Residential Roofs

1.2. Relevant identified uses of the substance or mixture and uses advised against Intended use

See Technical Data Sheet
Application Method

See Technical Data Sheet

1.3. Details of the supplier of the safety data sheet

Company Name Palmer Asphalt Company

196 West 5th St., P.O. Box 58

Bayonne, NJ 07002

Emergency Telephone No. (201) 339-0855

8:00a.m. - 5:00p.m. EST

After Hours CHEMTREC:

(800) - 424-9300 (Domestic - No. America)

SECTION 2 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

Product Description: This product is a viscous liquid in various colors including white, tan, light gray, dark gray and black with a slight odor.

Health Hazards: Exposure to the product may cause skin and eye irritation. Prolonged exposure may cause skin sensitization. Ingestion is not a normal route of exposure under normal product use. If swallowed, product may cause gastrointestinal irritation. This product contains an ingredient that is suspected of causing cancer and/or reproductive harm.

Flammability Hazards: This product has a flash point of >140°F and does not sustain combustion.

Reactivity Hazards: None known.

Environmental Hazards: The environmental effects of this product have not been investigated; however it is expected to cause adverse effects in the environment.

Emergency Considerations: Emergency responders must wear the proper personal protective equipment (and have appropriate fire-suppression equipment) suitable for the situation to which they are responding.

US DOT SYMBOLS

See Section 14 for Details

GHS Hazard Symbols





Signal Word: Warning!

#205 Bulldog One Coat Silicone Coating for Residential Roofs

SDS Revision Date: 6/28/2022



GHS Hazard Classification(s):

Flammable liquid Category 4

Skin Irritation Category 2

Eye Irritation Category 2A

Skin Sensitization Category 1

Carcinogenicity Category 2

Reproductive Toxicity Category 2

Specific Target Organ Toxicity Category 3 (Respiratory Irritation)

Chronic Aquatic Toxicity Category 3

Hazard Statement(s):

H227: Combustible liquid

H315: Causes skin irritation

H319: Causes serious eye irritation

H317: May cause and allergic skin reaction

H351: Suspected of causing cancer

H361: Suspected of damaging fertility or the unborn child

H335: May cause respiratory irritation.

H412: Harmful to aquatic life with long lasting effects

Prevention Statement(s):

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P272: Contaminated work clothing should not be allowed out of the workplace.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response Statement(s):

P370+P378: In case of fire: Use media defined in Section 5 to extinguish.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P302+P352: IF ON SKIN: Wash with plenty of water.

P321: Specific treatment (See Section 4 of this SDS).

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312: Call a POISON CENTER/doctor if you feel unwell.

#205 Bulldog One Coat Silicone Coating for Residential Roofs

SDS Revision Date: 6/28/2022



Storage Statement(s):

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

Disposal Statement(s):

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

HEALTH HAZARDS OR RISKS FROM EXPOSURE:

This product does not meet the criteria for PBT or vPvB in accordance with Annex XIII

ACUTE: This material may cause irritation to skin, eye, and respiratory system. May cause skin sensitization. Ingestion of this product may cause gastrointestinal irritation. This product contains an ingredient(s) that are suspected of causing reproductive harm.

CHRONIC: Prolonged or repeated skin contact may cause skin reactions.

TARGET ORGANS:

ACUTE: Eye, Skin, Respiratory System

CHRONIC: Respiratory System

#205 Bulldog One Coat Silicone Coating for Residential Roofs

SDS Revision Date: 6/28/2022



SECTION 3 - COMPOSITION and INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS:	CAS#	EINECS#	ICSC#	WT %	GHS HAZARD CLASSIFICATION(S):
Liquid Silicone Polymer	*Trade Secret	Not Listed in ESIS	Not Listed	45 – 60%	Not Classified
Nepheline Syenite	37244-96-5	609-369-8	Not Listed	15 – 30%	H335: STOT SE Cat 3 (Resp Irrit)
Titanium Dioxide	13463-67-7	236-675-5	0338	0 – 10%	H351: Carcinogenic Cat 2
Octamethylcyclotetrasiloxane	556-67-2	209-136-7	0310	1 – 10%	H361: Reproductive Toxicity Cat 2, H412: Chronic Aquatic Toxicity Cat 2
2-Butanone,O,O', O"- (Methylsilylidyne)Trioxime	22984-54-9	245-366-4	Not Listed	1 – 10%	H315: Skin Irrit Cat 2, H319: Eye Irrit. Cat 2, H317: Skin Sens Cat 1
Silica, Amorphous, fumed, crystal-free	112945-52-5	601-216-3	Not Listed	1 – 5%	H315: Skin Irrit Cat 2, H319: Eye Irrit. Cat 2, H335: STOT SE Cat 3 (Resp irrit)
2-Butanone, O,O',O"- silanetetrayltetraoxime	34206-40-1	251-882-0	Not Listed	<1%	H315: Skin Irrit Cat 2, H319: Eye Irrit. Cat 2, H317: Skin Sens Cat 1
Balance of other ingredients are carcinogens, reproductive toxins,			in concentration ((or 0.1% for	

^{*} Ingredients are Company Trade Secret - Business Confidential. Palmer Asphalt Company is withholding the specific chemical information under provision of the OSHA Hazard Communication Rule Trade Secrets (1910.1200(i)(1)). The specific chemical information will be made available to health professionals in accordance with 29 CFR 1910.1200 (i)(1) (2) (3) (4).

SECTION 4 - FIRST-AID MEASURES

EYE CONTACT: If product enters the eyes, open eyes while under gentle running water for at least 15 minutes. Seek medical attention if irritation develops.

SKIN CONTACT: Wash skin thoroughly after handling. Seek medical attention if irritation develops and persists. Remove contaminated clothing. Launder contaminated clothing before re-use.

INHALATION: If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention if breathing difficulty continues.

INGESTION: If product is swallowed, call physician or poison control center for most current information. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. Seek medical advice. Take a copy of the label and/or MSDS with the victim to the health professional.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing skin, or eye problems may be aggravated by exposure to this product.

RECOMMENDATIONS TO PHYSICIANS: Treat symptoms and reduce over-exposure.

#205 Bulldog One Coat Silicone Coating for Residential Roofs

SDS Revision Date: 6/28/2022



SECTION 5 - FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS (in air by volume, %): Lower Not Established Upper Not Established

(LEL): (UEL):

FIRE EXTINGUISHING MATERIALS: Carbon dioxide, foam, dry chemical, halon, water spray, sand,

limestone powder.

UNUSUAL FIRE AND EXPLOSION This material has been tested to ASTM D-4206 Standard and found

HAZARDS: not to sustain combustion

Explosion Sensitivity to Mechanical Impact: Not Sensitive.

Explosion Sensitivity to Static Discharge: Not Sensitive

SPECIAL FIRE-FIGHTING PROCEDURES: Incipient fire responders should wear eye protection. Structural

firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of


water, or other environmentally sensitive areas.

#205 Bulldog One Coat Silicone Coating for Residential Roofs

SDS Revision Date: 6/28/2022



NFPA RATING SYSTEM



ASPHALT CO

HMIS RATING SYSTEM HAZARDOUS MATERIAL IDENTIFICATION SYSTEM HEALTH HAZARD (BLUE) PHYSICAL HAZARD (YELLOW) PROTECTIVE EQUIPMENT EYES RESPIRATORY HANDS BODY See Sect 8 For Routine Industrial Use and Handling Applications

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

SECTION 6 - ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK RESPONSE: Personnel should be trained for spill response operations.

SPILLS: Contain spill if safe to do so. Prevent entry into drains, sewers, and other waterways. Soak up with a non-combustible absorbent material and place in an appropriate container for disposal. Dispose of in accordance with applicable Federal, State, and local procedures (see Section 13, Disposal Considerations).

SECTION 7 - HANDLING and STORAGE

WORK PRACTICES AND HYGIENE PRACTICES: As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash thoroughly after handling this product. Do not eat, drink, smoke, or apply cosmetics while handling this product. Avoid breathing vapors/mists generated by this product. Use in a well-ventilated location. Remove contaminated clothing immediately.

STORAGE AND HANDLING PRACTICES: Keep container tightly closed and in a dry and cool place.

#205 Bulldog One Coat Silicone Coating for Residential Roofs

SDS Revision Date: 6/28/2022



SECTION 8 - EXPOSURE CONTROLS - PERSONAL PROTECTION

EXPOSURE LIMITS/GUIDELINES:

Chemical Name	CAS#	ACGIH TWA	OSHA TWA	WEEL
Liquid Silicone Polymer	Non-Hazardous	Not Listed	Not Listed	Not Listed
Nepheline Syenite	37244-96-5	Not Listed	Not Listed	Not Listed
Titanium Dioxide	13463-67-7	10 mg/m³	10 mg/m³	10 mg/m³
Octamethylcyclotetrasiloxane	556-67-2	Not Listed	Not Listed	Not Listed
2-Butanone,O,O', O"- (Methylsilylidyne)Trioxime	22984-54-9	Not Listed	Not Listed	Not Listed
Silica, Amorphous, fumed, crystal- free	112945-52-5	Not Listed	Not Listed	Not Listed
2-Butanone, O,O',O"- silanetetrayItetraoxime	34206-40-1	Not Listed	Not Listed	Not Listed

Currently, International exposure limits are not established for the components of this product. Please check with competent authority in each country for the most recent limits in place.

VENTILATION AND ENGINEERING CONTROLS: Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above. Use local exhaust ventilation to control airborne vapor. Ensure eyewash/safety shower stations are available near areas where this product is used.

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standard of Canada, or standards of EU member states (including EN 149 for respiratory PPE, and EN 166 for face/eye protection), and those of Japan. Please reference applicable regulations and standards for relevant details.

RESPIRATORY PROTECTION: Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states.

EYE PROTECTION: Safety glasses or chemical goggles as appropriate to prevent eye contact. If necessary, refer to U.S. OSHA 29 CFR 1910.133 or appropriate Canadian Standards.

HAND PROTECTION: Use chemical resistant gloves to prevent skin contact. If necessary, refer to U.S. OSHA 29 CFR 1910.138 or appropriate Standards of Canada.

BODY PROTECTION: Use body protection appropriate to prevent contact (e.g. lab coat, overalls). If necessary, refer to appropriate Standards of Canada, or appropriate Standards of the EU, Australian Standards, or relevant Japanese Standards.

#205 Bulldog One Coat Silicone Coating for Residential Roofs

SDS Revision Date: 6/28/2022



SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

APPEARANCE & ODOR: Viscous liquid in various colors including white, tan, light

gray, dark gray and black with a slight odor.

Not Available ODOR THRESHOLD (PPM):

>140°F (This product has been tested to the ASTM D-4206

Standard and determined that it does not sustain

combustion) **AUTOIGNITION TEMPERATURE:** Not Established **VAPOR PRESSURE (mmHg):** Not Available Not Available **VAPOR DENSITY: EVAPORATION RATE (nBuAc = 1):** Not Available **BOILING POINT (C°):** Not Available FREEZING POINT (C°): Not Available pH: Not Available SPECIFIC GRAVITY 20°C: (WATER =1) Not Available **SOLUBILITY IN WATER (%)** Not Available

EXPLOSIVE PROPERTIES: Not Available **OXIDISING PROPERTIES:** Not Available

SECTION 10 - STABILITY and REACTIVITY

STABILITY: Product is stable

DECOMPOSITION PRODUCTS: When heated to decomposition this product produces noxious gases such as CO,

CO₂, and others.

FLASH POINT:

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: None known

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Heat and sources of ignition.

#205 Bulldog One Coat Silicone Coating for Residential Roofs

SDS Revision Date: 6/28/2022



SECTION 11 - TOXICOLOGICAL INFORMATION

TOXICITY DATA:

	-			
Chemical Name	al Name CAS#		Dermal LD50	Inhalation LC50
Liquid Silicone Polymer	Non- Hazardous	No Data	No Data	No Data
Liquid Officerie i Olymci	37244-96-5	No Data	No Data	No Data
Nepheline Syenite	37244-90-3		NO Data	NO Data
Titanium Dioxide	13463-67-7	>10000 mg/kg	No Data	No Data
Octamethylcyclotetrasiloxane	556-67-2	1540 mg/kg	>2400 mg/kg	36 gm/m³/4H
2-Butanone,O,O', O"-	22984-54-9	No Data	No Data	No Data
(Methylsilylidyne)Trioxime				
Silica, Amorphous, fumed, crystal-free	112945-52- 5	3160 mg/kg	No Data	No Data
	34206-40-1	No Data	No Data	No Data
2-Butanone, O,O',O"- silanetetrayltetraoxime				

Acute toxicity	Based on available data, the classification criteria are not met
Skin corrosion / irritation	Skin Irritation Category 2
Serious eye damage / irritation	Eye Irritation Category 2A
Respiratory or skin sensitization	Skin Sensitization Category 1
Germ cell mutagenicity	Based on available data, the classification criteria are not met
Carcinogenicity	Carcinogenicity Category 2
Reproductive toxicity	Reproductive Category 2
STOT-single exposure	Specific Target Organ Toxicity – Single Exposure (Respiratory Irritation)
STOT-repeated exposure	Based on available data, the classification criteria are not met
Aspiration hazard	Based on available data, the classification criteria are not met
·	

#205 Bulldog One Coat Silicone Coating for Residential Roofs

SDS Revision Date: 6/28/2022



SECTION 12 - ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

TOXICITY: No specific data is currently available on this product's effects on aquatic life, however release of this product may have long term effects on the aquatic environment.

Specific Component Data:

Octamethylcyclotetrasiloxane (556-67-2)
Test & Species Conditions
96 Hr LC50 Brachydanio rerio >500 mg/L
96 Hr LC50 Lepomis macrochirus >1000 mg/L
24 Hr EC50 Daphnia magna 25.2 mg/L

PERSISTENCE AND DEGRADABILITY: No specific data available on this product.

BIOACCUMULATIVE POTENTIAL: No specific data available on this product.

MOBILITY IN SOIL: No specific data available on this product.

RESULTS OF PBT AND vPvB ASSESMENT: No specific data available on this product.

OTHER ADVERSE EFFECTS: No specific data available on this product.

WATER ENDANGERMENT CLASS: Not believed to be water endangering in accordance with EU Guideline 91/155-EWG. At present there are no ecotoxicological assessments for this product.

SECTION 13 - DISPOSAL CONSIDERATIONS

PREPARING WASTES FOR DISPOSAL: Waste disposal must be in accordance with appropriate Federal, State, and local regulations, those of Canada, Australia, EU Member States and Japan.

RCRA WASTE CODE: None listed

EU WASTE CODE: Not Listed

#205 Bulldog One Coat Silicone Coating for Residential Roofs

SDS Revision Date: 6/28/2022



SECTION 14 - TRANSPORTATION INFORMATION

US DOT; IATA; IMO; ADR:

ASPHALT CO.

THIS PRODUCT IS CLASSIFIED AS DANGEROUS GOODS AS DEFINED BY 49 CFR 172.101 BY THE U.S. DEPARTMENT OF TRANSPORTATION.

This product has been tested to the ASTM D-4206 Standard and determined that it does not sustain combustion. As result it is exempt from regulations when shipped ground or rail within the U.S.A.

PROPER SHIPPING NAME: Non-Regulated when shipped ground or rail with U.S.A.

HAZARD CLASS NUMBER and DESCRIPTION: None

UN IDENTIFICATION NUMBER: None

PACKING GROUP: None

DOT LABEL(S) REQUIRED: None

NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER (2016): None

MARINE POLLUTANT: This product's ingredients that are not classified by the DOT as a Marine Pollutant (as defined

by 49 CFR 172.101, Appendix B)

TRANSPORT CANADA, TRANSPORTATION OF DANGEROUS GOODS REGULATIONS:

This product is not classified as Dangerous Goods, per regulations of Transport Canada.

INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA):

This product is not classified as Dangerous Good by International Air Transport.

INTERNATIONAL MARITIME ORGANIZATION (IMO) DESIGNATION:

This product is not classified as Dangerous Goods by the International Maritime Organization.

<u>EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY ROAD</u> (ADR):

This product is not classified by the United Nations Economic Commission for Europe to be dangerous goods. Harmonized Tariff Code Not Listed

SECTION 15 - REGULATORY INFORMATION

UNITED STATES REGULATIONS

SARA REPORTING REQUIREMENTS: This product is not subject to the reporting requirements of Sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act., as follows: None

TSCA: All components in this product are listed on the US Toxic Substances Control Act (TSCA) inventory of chemicals. **SARA 311/312:**

Acute Health: Yes Chronic Health Yes Fire: Yes Reactivity: No

<u>U.S. SARA THRESHOLD PLANNING QUANTITY:</u> There are no specific Threshold Planning Quantities for this product. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) may apply, per 40 CFR 370.20.

#205 Bulldog One Coat Silicone Coating for Residential Roofs

SDS Revision Date: 6/28/2022



U.S. CERCLA REPORTABLE QUANTITY (RQ): None

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65):

WARNING This product can expose you to chemicals such as Titanium Dioxide, which is known to the State of California as a cancer hazard if in respirable form. For more information, go to WWW.P65Warning.ca.gov

CANADIAN REGULATIONS:

ASPHALT CO.

CANADIAN DSL/NDSL INVENTORY STATUS: All of the components of this product are on the DSL Inventory CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS: No component of this product is on the CEPA First Priorities Substance Lists.

CANADIAN WHMIS CLASSIFICATION and SYMBOLS: Classified per WHMIS 2015

EUROPEAN ECONOMIC COMMUNITY INFORMATION:

EU LABELING AND CLASSIFICATION:

Classification of the mixture according to Regulation (EC) No1272/2008. See section 2 for details.

AUSTRALIAN INFORMATION FOR PRODUCT:

AUSTRALIAN INVENTORY OF CHEMICAL SUBSTANCES (AICS) STATUS: All components of this product are listed or exempt from listing on the AICS.

STANDARD FOR THE UNIFORM SCHEDULING OF DRUGS AND POISONS: Not applicable.

JAPANESE INFORMATION FOR PRODUCT:

JAPANESE MINISTER OF INTERNATIONAL TRADE AND INDUSTRY (MITI) STATUS: The components of this product are not listed as Class I Specified Chemical Substances, or Designated Chemical Substances by the Japanese MITI.

INTERNATIONAL CHEMICAL INVENTORIES:

Listing of the components on individual country Chemical Inventories is as follows:

Asia-Pac:

Australian Inventory of Chemical Substances (AICS):

Korean Existing Chemicals List (ECL):

Japanese Existing National Inventory of Chemical Substances (ENCS):

Philippines Inventory if Chemicals and Chemical Substances (PICCS):

Swiss Giftliste List of Toxic Substances:

Listed or exempt from listing

U.S. TSCA: Listed

SECTION 16 - OTHER INFORMATION

PREPARED BY: Tammy Cabrera

Disclaimer: The information and recommendations in this document are accurate to the best of our knowledge. User must conduct their own tests to determine the suitability of these products for their particular purposes. Because of numerous factors affecting results, Palmer Asphalt Company MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR PURPOSE, other than the material conforms to our applicable current specifications. Palmer Asphalt Company assumes no legal responsibility for use or reliance on the information contained in this Safety Data Sheet.

End of SDS Sheet

June 2022 Page 12 of 12